

TU SE 3.0 Series

Thermal Imaging Scope

outdoor

LPVO, Small but Mighty

Features

- o **Ultimate Clarity:** High-sensitivity infrared detector × Hyper-light intelligent image enhancement algorithm.
- o **Shutterless Design:** Innovative 3.0 shutterless design ensures smooth, uninterrupted visuals.
- o **Seamless Control:** Centrally positioned focus wheel & zoom lever, ergonomically designed for effortless operation.
- o **Ultra-Lightweight:** Only 575g, effortlessly portable.
- o **Rugged Design:** IP68-rated, shock resistance up to 6000J.
- o **Smart Recording:** Auto-saves video/photo per shot, capturing shooting moments.
- o **Smart Connectivity:** Dual-band Wi-Fi connection, OTA upgrade via TargetIR APP.

Applications

- o Night Hunting
- o Law Enforcement
- o Search & Rescue
- o Personal security



Specifications

Product model	TU425SE 3.0
Sensor	
Type	Uncooled VOx Infrared Detector, 8 to 14μm
Resolution	400×300@12μm
NETD	20mK
Frame rate	50 Hz
Lens	
Objective lens	25mm, F1.0
Field of view	10.3°×6.2°
FOV m@100m	18×11
Magnification	3.1x~12.4x
Detection range	1300m/1400yd
Focus	Manual
Display	
Display type	0.49" AMOLED 1920×1080
Color palettes	White Hot, Black Hot, Red Hot, Green Hot, Iron Red, Blue Hot, Sepia
Eyepiece	Eye relief: 48mm; Diopter -5 to +5; Zoom: 14x
Hardware	
WIFI	2.4G, 5G
Interface	USB-C (Charge/USB2.0)
Tube diameter	Standard 30 mm
Others	Microphone, Bluetooth
System	
Recording function	Photo/Video (Audio recording included)
Memory capacity	32GB
Power	
Battery type	18500 ×1 Battery (Built-in) and 18650 ×1 Battery (External)
Operating time	12 hours
Environmental	
Operating temp.	-20°C to 50°C / -4°F to +122°F
Shock	6000J/1200G
Encapsulation	IP68
Physical	
Weight (g/oz)	575/20.28
Size (mm/in)	311×89×76/12.24×3.50×2.99
Standard	Device, Lens Cover, Eye Mask, Quick-Release Scope Mount, Carry Bag, 18650 Battery ×2, Battery Charger, 5V 2A Adapter (US or UK or Australia or Europe), USB-A to USB-C Cable, Quick Start Guide, Warranty Card
Optional	Bluetooth Remote Control, Laser Rangefinder, 18650 Battery

* Product performance is based on testing in a controlled laboratory environment. Your test results may vary due to several external and environmental factors. All specifications are subject to the actual product. The manufacturer reserves the right to modify technical specifications without notice or liability to you.